FITTINGS

STANDARD DOUBLE Y'S


- 2-1/8" through 6" OD
- Wall Thickness: 16, 14, (11 Gauge Available in Straight Ends Only)
- (16 Gauge: 2-1/8" to 4" OD) (14 Gauge: 5" to 6" OD)
- · Materials: Carbon, Stainless, Aluminum, Galvanized Steel

STANDARD DOUBLE 90° TY'S

- 11 GAUGE TY'S AVAILABLE (STRAIGHT ENDS ONLY)
- · STRAIGHT AND EXPANDED COMBINATIONS AVAILABLE
- STRAIGHT ENDS AVAILABLE ON ALL SIZES BY REQUEST

	SIZE	GAUGE	A (OD)	В	C	F (OD)	Н	K	PART NO.
2-	1/8"	16	2-1/8"	5"	9-5/32"	2-1/8"	8-13/16"	9-1/2"	DTY-215
2-	1/2"	16	2-1/2"	6"	10-1/2"	2-1/2"	10-1/32"	10"	DTY-256
3"		16	3"	7-1/2"	12-3/8"	3"	11-25/32"	11-1/2"	DTY-307
3-	1/2"	16	3-1/2"	8-3/4"	14-1/8"	3-1/2"	13-11/32"	13"	DTY-358
4"		16	4"	10"	15-7/8"	4"	14-29/32"	14"	DTY-409
5"		14	5"	12-1/2"	19-3/8"	5"	18-5/8"	18-1/2"	DTY-515
6"		14	6"	15"	22-7/8"	6"	22-11/32"	21"	DTY-615

• EXPANDED ENDS STANDARD



STANDARD DOUBLE 90° TY

STANDARD DOUBLE 45° YL'S

- 11 GAUGE YL'S AVAILABLE (STRAIGHT ENDS ONLY)
- · STRAIGHT AND EXPANDED COMBINATIONS AVAILABLE
- · STRAIGHT ENDS AVAILABLE ON ALL SIZES BY REQUEST

SIZE	GAUGE	A (OD)	В	C	F (OD)	Н	K	PART NO.
2-1/8"	16	2-1/8"	5"	9-3/32"	2-1/8"	4-11/16"	9-1/2"	DYL-2151
2-1/2"	16	2-1/2"	6"	10-5/32"	2-1/2"	5-3/16"	10"	DYL-2561
3"	16	3"	7-1/2"	11-19/32"	3"	5-29/32"	11-1/2"	DYL-3071
3-1/2"	16	3-1/2"	8-3/4"	12-31/32"	3-1/2"	6-9/16"	13"	DYL-3581
4"	16	4"	10"	14-11/32"	4"	7-1/4"	14"	DYL-4091
5"	14	5"	12-1/2"	17-9/16"	5"	9"	18-1/2"	DYL-5151
6"	14	6"	15"	20-25/32"	6"	10-15/32"	21"	DYL-6151

• EXPANDED ENDS STANDARD

STANDARD DOUBLE 90° Y'S

- 11 GAUGE Y'S AVAILABLE (STRAIGHT ENDS ONLY)
- STRAIGHT AND EXPANDED COMBINATIONS AVAILABLE
- STRAIGHT ENDS AVAILABLE ON ALL SIZES BY REQUEST

SIZE	GAUGE	A (OD)	В	C	F (OD)	Н	K	PART NO.
2-1/8"	16	2-1/8"	5"	7"	2-1/8"	7"	-	DY-215
2-1/2"	16	2-1/2"	6"	8"	2-1/2"	8"	-	DY-256
3"	16	3"	7-1/2"	9-1/2"	3"	9-1/2"	-	DY-307
3-1/2"	16	3-1/2"	8-3/4"	10-3/4"	3-1/2"	10-3/4"	-	DY-358
4"	16	4"	10"	12"	4"	12"	-	DY-409
5"	14	5"	12-1/2"	15-1/8"	5"	15-1/8"	-	DY-515
6"	14	6"	15"	18-1/4"	6"	18-1/4"	-	DY-615

• EXPANDED ENDS STANDARD

C B L

STANDARD DOUBLE 45° YL

STANDARD DOUBLE 90° Y

KEY

OD = Outside Diameter

D = Expansion Depth 1-3/8" through 4" OD, 1-5/8" for 5" and 6" OD

A = Outside Diameter (OD) = E Inside Diameter (ID)

F = Outside Diameter (OD) = G Inside Diameter (ID)

L = Expansion Depth 1-3/8" through 4" OD, 1-5/8" for 5" and 6" OD

All reference dimensions are nominal.

WHEN ORDERING, PLEASE SPECIFY TYPE OF MATERIAL

- Carbon
- StainlessAluminum
- Galvanized Steel