



Arco Wand Double Tank Series Flux Recovery Units

Stationary

1 ½ - 7 ½ HP Continuous duty double tank flux recovery units for heavy duty welding applications.



Arco Wand Series Common Features:

- **Positive displacement vacuum pump**
- High Vacuum 7.5 to 9.0" Hg
- TEFC 1800 rpm high efficiency motor
- **Highest recovery rate on the market**
- Filter efficiency of **99% @ 0.4 microns**, standard
- Slag Screen, 2" Manual dump valve
- Vacuum relief valve – prevents motor overload
- Attached flux recovery hopper
- Totally enclosed – Panels on all sides
- Powder coat finish paint

Optional Features:

- Recovery from multiple welding heads
- Complete line of pick-up tools
- Flux band heaters available
- Specially fabricated overhead separators

ARCO WAND Series Model Specific Features

	6552-S	6882-S	6992-S	61002-S	61202-S
System Horsepower	1.5 HP	2.0 HP	3.0 HP	5 HP	7 ½ HP
Recovery rate with 1-1/2" x 25' Hose	40 lbs per min	45 lbs per min	55 lbs per min	60 lbs per min	75 lbs per min
Vacuum	7.0"HG (96"H2O)	7.0 "HG (96"H2O)	8.0" HG (110" H2O)	8.0"HG (110"H2O)	9.0 "HG (124"H2O)
Voltage/Phase	230/460/3/60	230/460/3/60	230/460/3/60	230/460/3/60	230/460/3/60
Dimensions L, W , H	76" x 30"x 56"	76" x 30"x 56"	76" x 30"x 56"	76" x 30"x 56"	76" x 30"x 56"
Hopper Capacity	150 lbs	150 lbs	150 lbs	150 lbs	150 lbs
Noise Level @ 3ft	75 DBA	77 DBA	78 DBA	78-80 DBA	81-83 DBA
Weight	630 lbs.	635 lbs.	730 lbs.	740 lbs.	760 lbs.